## NSN 5305-01-214-2690

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-214-2690 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.616 inches and 0.698 inches **Fastener Length:** Between 0.678 inches and 0.698 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.158 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c Minimum Yield Strength: 85000 pounds per square inch **Surface Finish:** 63.0 microinches bearing surface of head Material: Ams 5731 assn standard single material response

Iron alloy 660 **Material Specification: Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

## NSN 5305-01-214-2690

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0