

View Online at <https://aerobasegroup.com/nsn/5305-01-214-2691>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.480 inches and 0.500 inches

Fastener Length:

Between 1.600 inches and 1.630 inches

Head Height:

Between 0.306 inches and 0.313 inches

Width Between Flats:

Between 0.729 inches and 0.750 inches

Shoulder Diameter:

0.496 inches first shoulder and 0.498 inches first shoulder

Shoulder Length:

0.093 inches first shoulder

Single Shear Strength:

37300 pounds per square inch

Internal Drive Style:

Hexagon

End Application:

Missile, mx peacekeeper

Thread Diameter:

0.375 inches

Width Across Flats:

0.250 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 43.0 rockwell c

Shoulder Shape:

Round first shoulder

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2 class 3 federal specification single treatment response

Thread Series Designator:

Unrc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0