NSN 5305-01-214-5064

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-214-5064 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.382 inches and 0.412 inches **Fastener Length:** Between 1.007 inches and 1.037 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.464 inches and 0.507 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** 0.625 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No

NSN 5305-01-214-5064

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0