## NSN 5305-01-214-5066

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-214-5066 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.554 inches and 0.594 inches **Fastener Length:** Between 1.314 inches and 1.344 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.717 inches and 0.760 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 100.0 degrees **Surface Finish:** 32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas666 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-01-214-5066

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0