NSN 5305-01-214-5066

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-214-5066

| Thread Class: | |
|---|--|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 0.554 inches and 0.594 inches | |
| Fastener Length: | |
| Between 1.314 inches and 1.344 inches | |
| Head Style: | |
| Flat countersunk | |
| Head Diameter: | |
| Between 0.717 inches and 0.760 inches | |
| Grip Diameter: | |
| Between 0.3740 inches and 0.3745 inches | |
| Internal Drive Style: | |
| High-torque | |
| Thread Diameter: | |
| 0.375 inches | |
| Grip Length: | |
| Between 0.740 inches and 0.760 inches | |
| Thready Qty Per Inch (tpi): | |
| 24 | |
| Min. Tensile Strength (psi): | |
| 160000 pounds per square inch | |
| Countersink Angle: | |
| Between 99.0 degrees and 100.0 degrees | |
| Surface Finish: | |
| 32.0 microinches threads | |
| Material: | |
| Titanium alloy uns r56400 | |
| Material Specification: | |
| Ams4967 assn standard single material response | |
| Thread Series Designator: | |
| Unjf | |
| Specification Data: | |
| 80205-nas666 professional/industrial association standard | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

NSN 5305-01-214-5066

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

