NSN 5305-01-214-7875

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-214-7875

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.115 inches and 0.125 inches
Fastener Length:
Between 0.422 inches and 0.452 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.307 inches and 0.317 inches
Head Height:
Between 0.297 inches and 0.327 inches
Point Length:
0.078 inches
Point Diameter:
Between 0.062 inches and 0.078 inches
First Diameter From Head:
Between 0.073 inches and 0.083 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.224 inches and 0.244 inches
Point Style:
Cone
Internal Drive Style:
Slot
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Externally Relieved Body Diameter Quantity:
1
Point Chamfer Angle:
Between 85.0 degrees and 95.0 degrees
Special Features:
Color black; straight knurl
Material:
Steel comp 203ez or steel comp 303 or steel comp 303 plus x or steel comp 303ma or steel comp 303se or steel comp 416 or steel
comp 416 plus x or steel comp 416se or steel comp 430f or steel comp 430fse
Material Specification:
Astm a 581 assn standard all material responses

Oxide

Surface Treatment:

NSN 5305-01-214-7875

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0