

View Online at <https://aerobasegroup.com/nsn/5305-01-214-7896>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.225 inches and 1.275 inches

Fastener Length:

Between 2.075 inches and 2.105 inches

Head Style:

Flat countersunk

Head Diameter:

Between 1.047 inches and 1.146 inches

Grip Diameter:

Between 0.5635 inches and 0.5645 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.562 inches

Grip Length:

Between 0.830 inches and 0.850 inches

Thready Qty Per Inch (tpi):

18

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.