NSN 5305-01-215-0492

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-215-0492 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.481 inches **Fastener Length:** 0.560 inches **Head Style:** Flat extended washer **Head Diameter:** 0.249 inches **Head Height:** 0.060 inches **Extended Washer Diameter:** 0.370 inches **Extended Washer Thickness:** 0.060 inches **Locking Feature:** Strip locking feature Point Length: 0.125 inches **Point Diameter:** 0.124 inches First Diameter From Head: 0.250 inches **Second Diameter From Head:** 0.312 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.080 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.487 inches Point Style: Flat **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi):

NSN 5305-01-215-0492 Externally Relieved Body Screw - Page 2 of 2



Point Chamter Angle:
45.0 degrees
Special Features:
breakaway torque 6.5 in. Lbs., max torque 60 in. Lbs.
Material:
Stainless steel
Material Specification:
Qq-s-763, cl 202, 302, 304, condition b federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Jnef
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4003b0