

View Online at <https://aerobasegroup.com/nsn/5305-01-215-2489>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.250 inches

Fastener Length:

0.750 inches

Head Style:

Pan

Head Diameter:

0.219 inches

Head Height:

0.080 inches

Point Length:

0.070 inches

First Diameter From Head:

0.080 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.500 inches

Point Style:

Cone

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

80000 pounds per square inch

Externally Relieved Body Diameter Quantity:

1

Point Chamfer Angle:

120.0 degrees

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 1 federal specification single treatment response

Thread Series Designator:

UNF

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0