## NSN 5305-01-215-3773

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-215-3773 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 9.40 millimeters and 9.66 millimeters **Fastener Length:** 25.40 millimeters **Head Style:** Knurled no. 4 **Head Diameter:** Between 14.14 millimeters and 14.40 millimeters **Head Height:** Between 5.95 millimeters and 6.75 millimeters **First Diameter From Head:** Between 4.32 millimeters and 4.58 millimeters Distance From Largest Bearing Surface Of Head To End Of First Diameter: 15.87 millimeters **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response or astm a581 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-215-3773

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0