

View Online at <https://aerobasegroup.com/nsn/5305-01-215-3786>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.887 inches and 1.000 inches

**Fastener Length:**

Between 0.970 inches and 1.000 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.550 inches and 0.562 inches

**Head Height:**

Between 0.368 inches and 0.375 inches

**Hole Diameter:**

Between 0.061 inches and 0.067 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

Between 0.3125 inches and 0.3160 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

170000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c and 45.0 rockwell c

**Minimum Yield Strength:**

150000 pounds per square inch

**Hole Configuration Style:**

Round internal hexagon

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel

**Material Specification:**

66 federal specification single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924, class 3 military specification single treatment response

**Thread Series Designator:**

Unrf

**Specification Data:**

80205-nas1351 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.