NSN 5305-01-215-7283

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-215-7283 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.338 inches and 0.388 inches **Fastener Length:** Between 1.036 inches and 1.066 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.381 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads **Special Features:** Internal drive ribbed Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1580 professional/industrial association standard Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-215-7283

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0