NSN 5305-01-216-1327

Machine Screw - Page 1 of 2

Thread Class:

N/a



View Online at https://aerobasegroup.com/nsn/5305-01-216-1327

Tilleau Class.
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.501 inches and 1.625 inches
Fastener Length:
Between 1.563 inches and 1.625 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.306 inches and 0.313 inches
Head Height:
Between 0.103 inches and 0.118 inches
Hole Diameter:
Between 0.034 inches and 0.042 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.190 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Head Hole Configuration Style:
Round
Thread Series Designator:
Unjf
Specification Data:
80205-nas1101 professional/industrial association standard
Shelf Life:

NSN 5305-01-216-1327

Machine Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A500d0