## NSN 5305-01-216-3995

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-216-3995

/iew Online at https://aerobasegroup.com/nsn/5305-01-216-3995
Thread Class:
Pa
Thread Direction:
Right-hand
Fhread Length:
Between 0.530 inches and 0.630 inches
Fastener Length:
.000 inches
lead Style:
Double chamfer
lead Diameter:
0.500 inches
lead Height:
0.250 inches
Shoulder Diameter:
0.375 inches first shoulder
Shoulder Length:
0.370 inches first shoulder
Point Style:
Flat
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
20
Shoulder Shape:
Round first shoulder
Special Features:
Medium straight knurl on head; 0.062 in. Groove in shoulder, 0.125 in. Distance from end adjointing the threads; 0.112-40unc-2b threaded
nole by 0.250 in. Deep in center of head
Material:
Steel comp 316
Material Specification:
Mil-s-5059, cond a military specification single material response or qq-s-763, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type 1, type 2, type 3, type 6 federal specification single treatment response
Thread Series Designator:
Jnc
Shelf Life:
N/a
Jnit Of Measure:

--

## NSN 5305-01-216-3995

Thumbscrew - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.