

View Online at <https://aerobasegroup.com/nsn/5305-01-216-9054>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

1.750 inches

Fastener Length:

6.310 inches

Head Style:

Hexagon

Head Height:

0.480 inches

Width Between Flats:

0.312 inches

First Diameter From Head:

0.362 inches

Second Diameter From Head:

0.750 inches

Third Diameter From Head:

0.500 inches

Fourth Diameter From Head:

0.412 inches

Fifth Diameter From Head:

0.499 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

2.380 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

2.690 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

3.880 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

4.000 inches

Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:

5.440 inches

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

20

Criticality Code Justification:

Zzzy

Externally Relieved Body Diameter Quantity:

1

Distance From Largest Bearing Surface Of Head To End Of Sixth Diameter:

5.470 inches

Err Default:

Err default

Sixth Diameter From Head:

0.300 inches

Material:

Stainless steel

Material Specification:

Astma276-304 assn standard single material response

Thread Series Designator:

Unf

Reference Number Differentiating Characteristics:

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0