

View Online at <https://aerobasegroup.com/nsn/5305-01-217-2050>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.870 inches and 0.951 inches

**Fastener Length:**

Between 0.969 inches and 1.000 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.191 inches and 0.225 inches

**Locking Feature:**

Patch threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 302 or steel comp 303cu or steel comp 302b or steel comp 303ma or steel comp 303 or steel comp 304 or steel comp 303 plus x or steel comp 304l or steel comp 303se or steel comp 384 or steel comp 303 or steel comp 316 fastener

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Astm a380 assn standard single treatment response fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0