

View Online at <https://aerobasegroup.com/nsn/5305-01-217-2190>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.381 inches and 0.431 inches

**Fastener Length:**

Between 0.703 inches and 0.733 inches

**Head Style:**

Fillister countersunk

**Head Diameter:**

Between 0.2966 inches and 0.3016 inches

**Head Height:**

0.013 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches and 0.075 inches first hole

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.302 inches and 0.322 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.582 inches and 0.622 inches first hole

**Special Features:**

Cetyl alcohol lubrication

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Aluminum and chromate

**Surface Treatment Specification:**

Mil-c-83488, type2, class 3 military specification all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.