

View Online at <https://aerobasegroup.com/nsn/5305-01-217-5177>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.233 inches

**Fastener Length:**

1.000 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.105 inches and 0.120 inches

**Width Between Flats:**

Between 0.367 inches and 0.375 inches

**Internal Drive Style:**

Slot

**Material Accommodated Thickness:**

Between 0.188 inches and 0.250 inches

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Material:**

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 302b or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Material Specification:**

Qq-w-423 form 1 federal specification single material response spring

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response secondary washer

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5059 spec