

View Online at <https://aerobasegroup.com/nsn/5305-01-217-5987>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.303 inches

**Fastener Length:**

Between 0.372 inches and 0.375 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.296 inches and 0.331 inches

**Internal Drive Style:**

Tri-wing recess

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Steel comp 4340 or steel comp 8740

**Screw Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 military specification 2nd material response

**Screw Surface Treatment:**

Cadmium

**Screw Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas5602 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-5000 spec.