NSN 5305-01-217-7671

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-217-7671 **Thread Direction:** Right-hand Thread Length: Between 0.824 inches and 0.834 inches Fastener Length: Between 7.397 inches and 7.407 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.370 inches and 0.380 inches **Head Height:** Between 0.370 inches and 0.380 inches First Diameter From Head: Between 0.183 inches and 0.193 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 6.568 inches and 6.578 inches **Internal Drive Style:** Slot **Thread Diameter:** 6.0 millimeters **Thread Pitch In Millimeters:** 1.0 **Externally Relieved Body Diameter Quantity: Special Features:** Screwpoint u.S. Standard cone 90.0 degangle Material: Steel comp 303 **Material Specification:** Aisi national specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-e-16400 military specification single treatment response **Thread Series Designator:** Iso s Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-217-7671

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-e-16400 spec.