

View Online at <https://aerobasegroup.com/nsn/5305-01-217-7671>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.824 inches and 0.834 inches

**Fastener Length:**

Between 7.397 inches and 7.407 inches

**Head Style:**

Knurled no. 1

**Head Diameter:**

Between 0.370 inches and 0.380 inches

**Head Height:**

Between 0.370 inches and 0.380 inches

**First Diameter From Head:**

Between 0.183 inches and 0.193 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 6.568 inches and 6.578 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

6.0 millimeters

**Thread Pitch In Millimeters:**

1.0

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Screwpoint u.S. Standard cone 90.0 degangle

**Material:**

Steel comp 303

**Material Specification:**

Aisi national specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-e-16400 military specification single treatment response

**Thread Series Designator:**

Iso s

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-e-16400 spec.