
## NSN 5305-01-217-9057

Shoulder Screw - Page 1 of 2





## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.443 inches and 0.510 inches Fastener Length: Between 1.265 inches and 1.312 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.456 inches and 0.508 inches **Head Height:** Between 0.065 inches and 0.067 inches **Shoulder Diameter:** 0.2646 inches and 0.2651 inches first shoulder Shoulder Length: 0.7448 inches and 0.7468 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Cetyl alcohol lube; furnished with one o ring Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

---

## **NSN 5305-01-217-9057** Shoulder Screw - Page 2 of 2

Fiig: A003b0

