## NSN 5305-01-217-9059

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-217-9059



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.505 inches and 0.572 inches Fastener Length: Between 0.703 inches and 0.750 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.575 inches and 0.633 inches **Head Height:** Between 0.082 inches and 0.084 inches **Shoulder Diameter:** 0.3271 inches and 0.3276 inches first shoulder Shoulder Length: 0.1041 inches and 0.1061 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Cetyl alcohol lube and furnish with one o ring Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

---

## **NSN 5305-01-217-9059** Shoulder Screw - Page 2 of 2

Fiig: A003b0

