NSN 5305-01-218-1451

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-218-1451 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.505 inches and 0.572 inches **Fastener Length:** Between 0.765 inches and 0.812 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.575 inches and 0.633 inches **Head Height:** Between 0.075 inches and 0.077 inches **Shoulder Diameter:** 0.3427 inches and 0.3432 inches first shoulder **Shoulder Length:** 0.1731 inches and 0.1751 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Cetyl alcohol lube and furnish with one o ring Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-218-1451 Shoulder Screw - Page 2 of 2



Fiig:

A003b0