

View Online at <https://aerobasegroup.com/nsn/5305-01-218-1454>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.323 inches

Fastener Length:

Between 0.433 inches and 0.463 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.133 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

Cross recess type ii

Thread Diameter:

0.190 inches

Grip Length:

Between 0.115 inches and 0.135 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas7703 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.