

View Online at <https://aerobasegroup.com/nsn/5305-01-218-3138>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.126 inches and 1.314 inches

Fastener Length:

Between 2.906 inches and 3.000 inches

Head Style:

Hexagon

Head Height:

Between 0.272 inches and 0.291 inches

Width Between Flats:

Between 0.612 inches and 0.625 inches

Thread Diameter:

0.438 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Surface Finish:

63.0 microinches threads

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 or steel comp 303 plus x or steel comp 303cu or steel comp 303ma

Surface Treatment:

Passivate

Surface Treatment Specification:

Q-p-35 federal specification 13th treatment response

Thread Series Designator:

Unf

Specification Or Standard:

2 type and 10p style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0