

View Online at <https://aerobasegroup.com/nsn/5305-01-218-3147>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.380 inches and 0.447 inches

**Fastener Length:**

Between 0.890 inches and 0.937 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.427 inches and 0.467 inches

**Head Height:**

Between 0.068 inches and 0.070 inches

**Shoulder Diameter:**

0.217 inches and 0.218 inches first shoulder

**Shoulder Length:**

0.420 inches and 0.442 inches first shoulder

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Cetyl alcohol lube and furnished with synthetic rubber o-ring

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0