NSN 5305-01-218-3154

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-218-3154 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.505 inches and 0.572 inches **Fastener Length:** Between 0.827 inches and 0.874 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.575 inches and 0.633 inches **Head Height:** Between 0.075 inches and 0.077 inches **Shoulder Diameter:** 0.3427 inches and 0.3432 inches first shoulder **Shoulder Length:** 0.2251 inches and 0.2371 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Cetyl alcohol lube; furnished with one o ring Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-218-3154 Shoulder Screw - Page 2 of 2



Fiig:

A003b0