

View Online at <https://aerobasegroup.com/nsn/5305-01-219-2715>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.359 inches and 0.391 inches

**Fastener Length:**

Between 0.922 inches and 0.954 inches

**Head Style:**

Knurled no. 4

**Head Diameter:**

Between 0.557 inches and 0.567 inches

**Head Height:**

Between 0.234 inches and 0.266 inches

**First Diameter From Head:**

Between 0.147 inches and 0.157 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.531 inches and 0.595 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.216 inches

**Thready Qty Per Inch (tpi):**

24

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Straight knurl

**Material:**

Steel comp 303se or steel comp 416se or steel comp 430f or steel comp 303cu or steel comp 203ez or steel comp 303ma or steel comp 303 plus x or steel comp 430fse or steel comp 416 plus x or steel comp 303 or steel comp 416

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0