

View Online at <https://aerobasegroup.com/nsn/5305-01-219-2715>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.359 inches and 0.391 inches

Fastener Length:

Between 0.922 inches and 0.954 inches

Head Style:

Knurled no. 4

Head Diameter:

Between 0.557 inches and 0.567 inches

Head Height:

Between 0.234 inches and 0.266 inches

First Diameter From Head:

Between 0.147 inches and 0.157 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.531 inches and 0.595 inches

Internal Drive Style:

Slot

Thread Diameter:

0.216 inches

Thready Qty Per Inch (tpi):

24

Externally Relieved Body Diameter Quantity:

1

Special Features:

Straight knurl

Material:

Steel comp 303se or steel comp 416se or steel comp 430f or steel comp 303cu or steel comp 203ez or steel comp 303ma or steel comp 303 plus x or steel comp 430fse or steel comp 416 plus x or steel comp 303 or steel comp 416

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0