## NSN 5305-01-219-2930

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-219-2930 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.880 inches **Head Style:** Knurled no. 2 **Head Diameter:** 0.500 inches **Head Height:** Between 0.230 inches and 0.270 inches Point Length: 0.120 inches **Point Diameter:** Between 0.114 inches and 0.130 inches **First Diameter From Head:** 0.130 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.500 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** 60.0 degrees Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-01-219-2930

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0