

View Online at <https://aerobasegroup.com/nsn/5305-01-219-4124>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.222 inches

**Fastener Length:**

0.500 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

0.222 inches

**Head Height:**

0.136 inches

**First Diameter From Head:**

0.082 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.278 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.138 inches

**Width Across Flats:**

0.110 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell b

**Minimum Yield Strength:**

30000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Chamfer Angle:**

37.5 degrees

**Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

**Material Specification:**

N0.66 federal standard all material responses

**Surface Treatment:**

Passivate and oxide

**Surface Treatment Specification:**

Qq-p-35 federal specification 1st treatment response and mil-c-13924, class 4 military specification 2nd treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.