## NSN 5305-01-219-5399

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-219-5399 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.236 inches **Fastener Length:** Between 0.290 inches and 0.310 inches **Head Style:** Hexagon **Head Height:** Between 0.096 inches and 0.110 inches Width Between Flats: Between 0.305 inches and 0.312 inches Washer Quantity: **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.305 inches and 0.320 inches **Primary Washer Style:** Flat external and internal teeth **Primary Washer Material Thickness:** Between 0.018 inches and 0.023 inches Material: Steel **Surface Treatment:** Zinc **Surface Treatment Specification:** Gm 4342-m, code 10u8, fscm 24617 mfr ref single treatment response **Thread Series Designator:** Unrc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-219-5399

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0