Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-219-5401



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.185 inches and 0.265 inches Fastener Length: Between 0.235 inches and 0.265 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches Locking Feature: Patch threads **Internal Drive Style:** High-torque **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1216 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-219-5401

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

