## NSN 5305-01-219-5946

Close Tolerance Screw - Page 1 of 2

3a

32





**Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.338 inches and 0.388 inches Fastener Length: Between 1.660 inches and 1.690 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.360 inches and 0.374 inches **Head Height:** Between 0.115 inches and 0.125 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Grip Length: Between 1.302 inches and 1.322 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads **Special Features:** Internal drive ribbed Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 

80205-nas1578 professional/industrial association standard

## NSN 5305-01-219-5946

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

