## NSN 5305-01-219-7177

**Thread Class:** 

**Thread Direction:** 

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-219-7177

Right-hand
Thread Length:
Between 0.454 inches and 0.521 inches
Fastener Length:
Between 1.964 inches and 2.011 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.578 inches and 0.634 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.312 inches
Grip Length:
Between 1.490 inches and 1.510 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Product Name:
Navy special project
Special Features:
Internal drive ribbed
Material:
Steel comp h11
Material Specification:
Ams6487 assn standard single material response
Surface Treatment:
Cadmium or cadmium and chromate
Surface Treatment Specification:
Nas672 assn standard 1st treatment response or mil-c-8837, ty2, cl2 military specification 2nd treatment response

## NSN 5305-01-219-7177

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-c-8837 spec.