## NSN 5305-01-219-7180

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-219-7180 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.476 inches and 0.526 inches **Fastener Length:** Between 1.111 inches and 1.141 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.429 inches and 0.479 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads **Special Features:** Internal drive ribbed Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1581 professional/industrial association standard Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-219-7180

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0