NSN 5305-01-219-7183

Close Tolerance Screw - Page 1 of 2





View Online at https://aerobasegroup.com/nsn/5305-01-219-7183

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.476 inches and 0.526 inches
Fastener Length:
Between 0.986 inches and 1.016 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.4289 inches and 0.4787 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.312 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Special Features:
Internal drive ribbed
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1581 professional/industrial association standard
Shelf Life:
N/a

Unit Of Measure:

NSN 5305-01-219-7183

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

