## NSN 5305-01-219-8418

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-219-8418 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.013 inches and 1.125 inches **Fastener Length:** Between 1.063 inches and 1.125 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Stainless steel or steel **Screw Material Specification:** Qq-s-763, 300ser1es federal specification 1st material response or 66 federal standard 1st material response or com+16-18 or 18-8 federal standard all material responses **Screw Surface Treatment:** Passivate or oxide film **Screw Surface Treatment Specification:** Qq-p-35 federal specification 1st treatment response and mil-c-13924 cl4 military specification 2nd treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 1 type and 9c style Shelf Life: N/a **Unit Of Measure:** 

Fiig:

No

**Demilitarization:** 

A500d0

## NSN 5305-01-219-8418

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.