## NSN 5305-01-219-8418

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-219-8418



#### **Thread Class:**

2a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 1.013 inches and 1.125 inches

#### Fastener Length:

Between 1.063 inches and 1.125 inches

#### Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

#### **Head Height:**

Between 0.070 inches and 0.080 inches

#### Internal Drive Style:

Cross recess type 1

## Thread Diameter:

0.112 inches

0.112 inches

### Thready Qty Per Inch (tpi):

40

#### Min. Tensile Strength (psi):

80000 pounds per square inch

#### **Screw Material:**

Stainless steel or steel

#### Screw Material Specification:

Qq-s-763, 300ser1es federal specification 1st material response or 66 federal standard 1st material response or com+16-18 or 18-8 federal standard all material responses

#### **Screw Surface Treatment:**

Passivate or oxide film

## Screw Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response and mil-c-13924 cl4 military specification 2nd treatment response

## Thread Series Designator:

Unc

#### **Specification Or Standard:**

1 type and 9c style

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A500d0

# NSN 5305-01-219-8418

Machine Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-c-13924 spec.

