## NSN 5305-01-219-9598

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-219-9598 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.210 inches and 1.250 inches **Fastener Length:** Between 1.210 inches and 1.250 inches **Head Style:** Hexagon **Head Height:** Between 0.306 inches and 0.313 inches Width Between Flats: Between 0.457 inches and 0.469 inches **First Diameter From Head:** Between 0.208 inches and 0.212 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.029 inches and 0.032 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.3125 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 **Externally Relieved Body Diameter Quantity: Special Features:** Screw end rounded to 5/32 r and the item is altered from ms16995-67 Steel comp 302 and steel comp 303 and steel comp 304 and steel comp 305 and steel comp 316 **Material Specification:** 66 federal standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-219-9598

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0