NSN 5305-01-220-0199

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-220-0199 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.380 inches and 0.447 inches **Fastener Length:** Between 0.952 inches and 0.999 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.427 inches and 0.467 inches **Head Height:** Between 0.068 inches and 0.070 inches **Shoulder Diameter:** 0.217 inches and 0.218 inches first shoulder **Shoulder Length:** 0.482 inches and 0.504 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Cetyl alcohol lube Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-220-0199

Shoulder Screw - Page 2 of 2



Fiig:

A003b0