

View Online at <https://aerobasegroup.com/nsn/5305-01-220-0201>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.881 inches and 0.931 inches

Fastener Length:

Between 3.016 inches and 3.046 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.766 inches and 0.838 inches

Grip Diameter:

Between 0.5605 inches and 0.5615 inches

Shank Unthreaded Hole Diameter:

0.141 inches and 0.146 inches first hole

Internal Drive Style:

High-torque

Thread Diameter:

0.562 inches

Grip Length:

Between 2.115 inches and 2.135 inches

Thready Qty Per Inch (tpi):

18

Countersink Angle:

101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.887 inches and 2.927 inches first hole

Special Features:

Threads cetyl alcohol lubricated

Material:

Steel comp xm-13

Material Specification:

23-112, fscm 76301 mfr ref single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488, type 2, cl 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.