

View Online at <https://aerobasegroup.com/nsn/5305-01-220-6493>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.615 inches and 0.682 inches

**Fastener Length:**

Between 1.187 inches and 1.234 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.692 inches and 0.763 inches

**Head Height:**

Between 0.109 inches and 0.111 inches

**Shoulder Diameter:**

0.3896 inches and 0.3901 inches first shoulder

**Shoulder Length:**

0.4512 inches and 0.4532 inches first shoulder

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Cetyl alcohol lube and furnish with one o ring

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0