NSN 5305-01-220-6496



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-220-6496 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.443 inches and 0.510 inches **Fastener Length:** Between 1.328 inches and 1.375 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.456 inches and 0.508 inches **Head Height:** Between 0.058 inches and 0.060 inches **Shoulder Diameter:** 0.2802 inches and 0.2807 inches first shoulder **Shoulder Length:** 0.8048 inches and 0.8268 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Cetyl alcohol lube, furnished with one o-ring Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator: Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

NSN 5305-01-220-6496

Shoulder Screw - Page 2 of 2



Fiig:

A003b0