

View Online at <https://aerobasegroup.com/nsn/5305-01-220-6497>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.386 inches and 0.453 inches

Fastener Length:

Between 0.896 inches and 0.943 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.464 inches and 0.507 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.250 inches

Grip Length:

Between 0.490 inches and 0.510 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

220000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Product Name:

Navy special project

Special Features:

Internal drive ribbed

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium or cadmium and chromate

Surface Treatment Specification:

Nas672 assn standard 1st treatment response or mil-s-8837, ty2, cl2 military specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-8837 spec.