## NSN 5305-01-220-8680

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-220-8680



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.380 inches and 0.447 inches Fastener Length: Between 0.702 inches and 0.749 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.427 inches and 0.467 inches **Head Height:** Between 0.068 inches and 0.070 inches **Shoulder Diameter:** 0.217 inches and 0.218 inches first shoulder Shoulder Length: 0.232 inches and 0.254 inches first shoulder **Internal Drive Style:** High-torque Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Cetyl alcohol lube Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

---

## NSN 5305-01-220-8680

Shoulder Screw - Page 2 of 2

Fiig: A003b0

