## NSN 5305-01-220-9693

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-220-9693 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.240 inches and 0.250 inches **Fastener Length:** 1.125 inches **Head Style:** Double chamfer **Head Diameter:** Between 0.370 inches and 0.380 inches **Head Height:** Between 0.422 inches and 0.454 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.719 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Material Specification:** Astm a555 assn standard single material response or astm a581 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-220-9693

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.