

View Online at <https://aerobasegroup.com/nsn/5305-01-221-4198>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.360 inches and 0.390 inches

Fastener Length:

Between 0.730 inches and 0.770 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.350 inches and 0.390 inches

Head Height:

0.330 inches

Internal Drive Style:

Hexagon

Material Accommodated Thickness:

Between 0.090 inches and 0.100 inches

Thread Diameter:

0.250 inches

Width Across Flats:

0.187 inches

Thready Qty Per Inch (tpi):

28

Material:

Steel comp 301 fastener or steel comp 302 fastener or steel comp 302b fastener or steel comp 303 fastener or steel comp 303se fastener or steel comp 304 fastener or steel comp 304l fastener or steel comp 305 fastener or steel comp 308 fastener or steel comp 309 fastener or steel comp 309s fastener or steel comp 310 fastener or steel comp 310s fastener or steel comp 314 fastener or steel comp 316 fastener or steel comp 316l fastener or steel comp 317 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 348 fastener or steel comp 384 fastener or steel comp 385 fastener

Material Specification:

Qq-l-a-225/9 federal specification single material response stand-off

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

Mil-std (military Standard):

Mil-c-5541 spec.