## NSN 5305-01-221-8695

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-221-8695 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.880 inches and 1.190 inches **Fastener Length:** Between 1.609 inches and 1.656 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.160 inches and 0.164 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.1406 inches and 0.1426 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Minimum Yield Strength: 125000 pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5734 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-221-8695

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0